

Datenblatt für Verbundanlage aus Raumheizgerät oder Kombiheizgerät mit Wärmepumpe, Temperaturregler und Solareinrichtungen, Raumheizungs-Energieeffizienz

EcoTouch 5063.5T - brine to water

Abbildung 3

Bei Vorzugsraumheizgeräten mit Wärmepumpe und Vorzugskombiheizgeräten mit Wärmepumpe zur Angabe der jahreszeitbedingten Raumheizungs-Energieeffizienz der angebotenen Verbundanlage in das Datenblatt für eine Verbundanlage aus Raumheizgeräten, Temperaturreglern und Solareinrichtungen bzw. eine Verbundanlage aus Kombiheizgeräten, Temperaturreglern und Solareinrichtungen aufzunehmen

| | | |
|--|---|---|
| Jahreszeitbedingte Raumheizungs-Energieeffizienz der Wärmepumpe | | 1 159 % |
| Temperaturregler Vom Datenblatt des Temperaturreglers | + | 2 <div style="border: 1px solid black; padding: 5px; margin: 5px auto; width: fit-content;"> Klasse I = 1 %, Klasse II = 2 %, Klasse III = 1,5 %, Klasse IV = 2 %, Klasse V = 3 %, Klasse VI = 4 %, Klasse VII = 3,5 %, Klasse VIII = 5 % </div> 1,5 % |
| Zusatzheizkessel Vom Datenblatt des Heizkessels | - | 3 <div style="border: 1px solid black; padding: 5px; margin: 5px auto; width: fit-content;"> Jahreszeitbedingte Raumheizungs-Energieeffizienz in % (0 - 'I') x 'II' = </div> 0 % |
| Solarer Beitrag Vom Datenblatt der Solareinrichtung | + | 4 <div style="display: flex; justify-content: space-around; margin-bottom: 5px;"> <div style="border: 1px solid black; padding: 2px; font-size: small;">Kollektorgroße (in m²)</div> <div style="border: 1px solid black; padding: 2px; font-size: small;">Tankvolumen (in m³)</div> <div style="border: 1px solid black; padding: 2px; font-size: small;">Kollektorwirkungsgrad (in %)</div> <div style="border: 1px solid black; padding: 2px; font-size: small;">Tankeinstufung A+ = 0,95, A = 0,91, B = 0,86, C = 0,83, D-G = 0,81</div> </div> <div style="display: flex; justify-content: space-between; font-size: small;"> ('III' x 0 + 'IV' x 0) x 0,45 x (0 / 100) x 1 </div> 0 % |
| Jahreszeitbedingte Raumheizungs-Energieeffizienz der Verbundanlage bei durchschnittlichem Klima | | 5 161 |
| Jahreszeitbedingte Raumheizungs-Energieeffizienzklasse der Verbundanlage bei durchschnittlichem Klima | | |
| <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <input type="checkbox"/> G <small>< 30%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> F <small>≥ 30 %</small> </div> <div style="text-align: center;"> <input type="checkbox"/> E <small>≥ 34%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> D <small>≥ 36%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> C <small>≥ 75%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> B <small>≥ 82%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> A <small>≥ 90%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> A+ <small>≥ 98%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> A++ <small>≥ 125%</small> </div> <div style="text-align: center;"> <input checked="" type="checkbox"/> A+++ <small>≥ 150%</small> </div> </div> | | |
| Jahreszeitbedingte Raumheizungs-Energieeffizienz der Verbundanlage bei kälterem und wärmerem Klima | | 5 5 |
| Kälter: | - | -1 = 162 % |
| Wärmer: | + | -1 = 160 % |

Die auf diesem Datenblatt für den Produktverbund angegebene Energieeffizienz weicht möglicherweise von der Energieeffizienz nach dessen Einbau in ein Gebäude ab, denn diese wird von weiteren Faktoren wie dem Wärmeverlust im Verteilungssystem und der Dimensionierung der Produkte im Verhältnis zu Größe und Eigenschaften des Gebäudes beeinflusst.



ENERG

енергия · ενέργεια

Y

IJA



IE


IA


 WATERKOTTE


EcoTouch 5063.5T - brine to water





 

+ 

+ 

+ 

+ 


 



















Product fiche requirements for heat pump space heaters and heat pump combination heaters (in accordance with EU regulation no. 811/2013)

| | | | | | | | |
|---|---|---|-------|---------------|---------------|---------------|---------------|
| Supplier's name | | Waterkotte GmbH, Gewerkestr. 15, 44628 Herne, Germany | | | | | |
| Model(s): | 1 | EcoTouch 5063.5T, Brine/Water | | | | | |
| | 2 | EcoTouch 5075.5T, Brine/Water | | | | | |
| | 3 | EcoTouch 5085.5T, Brine/Water | | | | | |
| | 4 | EcoTouch 5095.5T, Brine/Water | | | | | |
| Item | | Symbol | Unit | 1 | 2 | 3 | 4 |
| Medium temperature / Low temperature | | | | 55°C / 35°C | 55°C / 35°C | 55°C / 35°C | 55°C / 35°C |
| Seasonal space heating energy efficiency class of the model | | - | 159 | A+++ / A+++ | A+++ / A+++ | A+++ / A+++ | A+++ / A+++ |
| Declared load profile for water heating | | - | - | - | - | - | - |
| Water heating energy efficiency class | | - | - | - | - | - | - |
| Rated heat output, including the rated heat output of any supplementary heater under average climate conditions | | P _{rated} | kW | 45 / 49 | 53 / 57 | 58 / 64 | 68 / 73 |
| Seasonal space heating energy efficiency under average climate conditions | | η _s | % | 159 / 213 | 161 / 219 | 159 / 214 | 161 / 211 |
| Space heating, annual energy consumption under average climate conditions | | Q _{HE} | kWh | 22458 / 18233 | 25821 / 20344 | 28856 / 23731 | 33014 / 27384 |
| Water heating energy efficiency | | η _{wh} | % | - | - | - | - |
| Water heating, the annual electricity consumption | | AEC | kWh | - | - | - | - |
| Sound power level L _{WA} , indoors | | L _{WA} | dB(A) | 66 | 69 | 69 | 70 |
| Any specific precautions that shall be taken when the heater is assembled, installed or maintained: see installation manual Alle beim Zusammenbau, der Installation oder Wartung des Raumheizgerätes zu treffenden besonderen Vorkehrungen: siehe Installationsanleitung Les éventuelles précautions particulières qui doivent être prises lors du montage, de l'installation ou de l'entretien du dispositif de chauffage des locaux: voir manuel d'installation | | | | | | | |
| Rated heat output, including the rated heat output of any supplementary heater under colder climate conditions | | P _{rated} | kW | 45 / 49 | 53 / 57 | 58 / 64 | 68 / 73 |
| Rated heat output, including the rated heat output of any supplementary heater under warmer climate conditions | | P _{rated} | kW | 45 / 49 | 53 / 57 | 58 / 64 | 68 / 73 |
| Seasonal space heating energy efficiency under colder climate conditions | | η _s | % | 160 / 217 | 165 / 224 | 163 / 218 | 165 / 215 |
| Seasonal space heating energy efficiency under warmer climate conditions | | η _s | % | 158 / 208 | 160 / 212 | 159 / 208 | 161 / 206 |
| Space heating, annual energy consumption under colder climate conditions | | Q _{HE} | kWh | 28678 / 21370 | 30141 / 24308 | 33741 / 27828 | 38619 / 32135 |
| Space heating, annual energy consumption under warmer climate conditions | | Q _{HE} | kWh | 14591 / 12097 | 16773 / 13960 | 18716 / 15757 | 21408 / 18122 |
| Sound power level L _{WA} , outdoors | | L _{WA} | dB(A) | - | - | - | - |

Information requirements for heat pump space heaters and heat pump combination heaters (in accordance with EU regulation no. 813/2013)

| | | | | | | | |
|-----------|---|-------------------------------|--|--|--|--|--|
| Model(s): | 1 | EcoTouch 5063.5T, Brine/Water | | | | | |
| | 2 | EcoTouch 5075.5T, Brine/Water | | | | | |
| | 3 | EcoTouch 5085.5T, Brine/Water | | | | | |
| | 4 | EcoTouch 5095.5T, Brine/Water | | | | | |
| | 5 | EcoTouch 5112.5T, Brine/Water | | | | | |

| | | | | | | |
|---|---|-------------------|----------|----------|----------|----------|
| | | 1 | 2 | 3 | 4 | 5 |
| Air-to-water heat pump | | - | - | - | - | - |
| Water-to-water heat pump | | - | - | - | - | - |
| Brine-to-water heat pump | | yes | yes | yes | yes | yes |
| Low-temperature heat pump | | - | - | - | - | - |
| Equipped with a supplementary heater | | - | - | - | - | - |
| Heat pump combination heater | | - | - | - | - | - |
| Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application. | | | | | | |
| Parameters shall be declared for average climate conditions. | | | | | | |
| Item | Symbol | Unit | 1 | 2 | 3 | 4 |
| Rated heat output (*) | P _{rated} | kW | 45 | 53 | 58 | 68 |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j | | | | | | |
| T _j = -7 °C | P _{dh} | kW | 40,2 | 46,7 | 51,7 | 59,8 |
| T _j = +2 °C | P _{dh} | kW | 25,2 | 29,5 | 32,8 | 37,5 |
| T _j = +7 °C | P _{dh} | kW | 25,5 | 30,0 | 33,3 | 38,0 |
| T _j = +12 °C | P _{dh} | kW | 26,0 | 30,7 | 34,1 | 38,9 |
| T _j = bivalent temperature | P _{dh} | kW | 45,4 | 52,8 | 58,4 | 67,6 |
| T _j = operation limit temperature | P _{dh} | kW | 45,4 | 52,8 | 58,4 | 67,6 |
| For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C) | P _{dh} | kW | - | - | - | - |
| Bivalent temperature | T _{biv} | °C | - | - | - | - |
| Cycling interval capacity for heating | P _{cyc} | kW | - | - | - | - |
| Degradation co-efficient (**) | C _{dh} | - | 1,0 | 1,0 | 1,0 | 1,0 |
| Seasonal space heating energy efficiency | η _s | % | 159 | 161 | 159 | 161 |
| Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j | | | | | | |
| T _j = -7 °C | COP _{pd} | - | 3,10 | 3,08 | 3,10 | 3,20 |
| T _j = +2 °C | COP _{pd} | - | 4,29 | 4,33 | 4,28 | 4,33 |
| T _j = +7 °C | COP _{pd} | - | 4,58 | 4,67 | 4,59 | 4,61 |
| T _j = +12 °C | COP _{pd} | - | 5,11 | 5,28 | 5,16 | 5,16 |
| T _j = bivalent temperature | COP _{pd} | - | 2,80 | 2,79 | 2,82 | 2,92 |
| T _j = operation limit temperature | COP _{pd} | - | 2,80 | 2,79 | 2,82 | 2,92 |
| For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C) | COP _{pd} | - | - | - | - | - |
| For air-to-water heat pumps: Operation limit temperature | TOL | °C | - | - | - | - |
| Cycling interval efficiency | COP _{cyc} | - | - | - | - | - |
| Heating water operating limit temperature | WTOL | °C | 55 | 55 | 55 | 55 |
| Power consumption in modes other than active mode | | | | | | |
| Off mode | P _{off} | kW | 0,001 | 0,001 | 0,001 | 0,001 |
| Thermostat-off mode | P _{to} | kW | 0,017 | 0,017 | 0,017 | 0,017 |
| Standby mode | P _{sb} | kW | 0,017 | 0,017 | 0,017 | 0,017 |
| Crankcase heater mode | P _{ck} | kW | - | - | - | - |
| Supplementary heater | | | | | | |
| Rated heat output (*) | P _{sup} | kW | - | - | - | - |
| Type of energy input | | | | | | |
| Other items | | | | | | |
| Capacity control | fixed/variable | | variable | variable | variable | variable |
| Sound power level, indoors/ outdoors | L _{WA} | dB(A) | 66 / - | 69 / - | 69 / - | 70 / - |
| Emissions of nitrogen oxides | NO _x | mg/kWh | - | - | - | - |
| For air-to-water heat pumps: Rated air flow rate, outdoors | | m ³ /h | - | - | - | - |
| For water-brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger | | m ³ /h | 9 | 11 | 12 | 14 |
| For heat pump combination heater: | | | | | | |
| Declared load profile | | | | | | |
| Daily electricity consumption | Q _{elec} | kWh | - | - | - | - |
| Water heating energy efficiency | η _{wh} | % | - | - | - | - |
| Daily fuel consumption | Q _{fuel} | kWh | - | - | - | - |
| Contact details | Waterkotte GmbH, Gewerkestr. 15, 44628 Herne, Germany | | | | | |

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output P_{rated} is equal to the design load for heating P_{design}, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(T_j).

(**) If C_{dh} is not determined by measurement then the default degradation coefficient is C_{dh} = 0,9.

Any specific precautions that shall be taken when the heater is assembled, installed or maintained: see installation manual
Information relevant for disassembly, recycling and/or disposal at end-of-life: see installation manual

Alle beim Zusammenbau, der Installation oder Wartung des Raumheizgerätes zu treffenden besonderen Vorkehrungen: siehe Installationsanleitung
Sachdienliche Angaben für das Zerlegen, die Wiederverwendung und/oder die Entsorgung nach der endgültigen Außerbetriebstellung: siehe Installationsanleitung

Les éventuelles précautions particulières qui doivent être prises lors du montage, de l'installation ou de l'entretien du dispositif de chauffage des locaux: voir manuel d'installation
Informations utiles pour le démontage, le recyclage et/ou l'élimination à la fin du cycle de vie de l'appareil: voir manuel d'installation

Datenblatt für Verbundanlage aus Raumheizgerät oder Kombiheizgerät mit Wärmepumpe, Temperaturregler und Solareinrichtungen, Raumheizungs-Energieeffizienz

EcoTouch 5063.5T - water to water

Abbildung 3

Bei Vorzugsraumheizgeräten mit Wärmepumpe und Vorzugskombiheizgeräten mit Wärmepumpe zur Angabe der jahreszeitbedingten Raumheizungs-Energieeffizienz der angebotenen Verbundanlage in das Datenblatt für eine Verbundanlage aus Raumheizgeräten, Temperaturreglern und Solareinrichtungen bzw. eine Verbundanlage aus Kombiheizgeräten, Temperaturreglern und Solareinrichtungen aufzunehmen

| | | |
|---|----------------|---|
| Jahreszeitbedingte Raumheizungs-Energieeffizienz der Wärmepumpe | | 1 211 % |
| Temperaturregler Vom Datenblatt des Temperaturreglers | + | 2 <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> Klasse I = 1 %, Klasse II = 2 %, Klasse III = 1,5 %, Klasse IV = 2 %, Klasse V = 3 %, Klasse VI = 4 %, Klasse VII = 3,5 %, Klasse VIII = 5 % </div> 1,5 % |
| Zusatzheizkessel Vom Datenblatt des Heizkessels | - | 3 <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> Jahreszeitbedingte Raumheizungs-Energieeffizienz in % (0 - 'I') x 'II' = </div> 0 % |
| Solarer Beitrag Vom Datenblatt der Solareinrichtung | + | 4 <div style="display: flex; justify-content: space-around; margin-bottom: 5px;"> <div style="border: 1px solid black; padding: 2px; font-size: small;">Kollektorgroße (in m²)</div> <div style="border: 1px solid black; padding: 2px; font-size: small;">Tankvolumen (in m³)</div> <div style="border: 1px solid black; padding: 2px; font-size: small;">Kollektorwirkungsgrad (in %)</div> <div style="border: 1px solid black; padding: 2px; font-size: small;">Tankeinstufung A+ = 0,95, A = 0,91, B = 0,86, C = 0,83, D-G = 0,81</div> </div> <div style="display: flex; justify-content: space-between; margin-bottom: 5px;"> ('III' x 0 + 'IV' x 0) x 0,45 x (0 / 100) x 1 </div> 0 % |
| Jahreszeitbedingte Raumheizungs-Energieeffizienz der Verbundanlage bei durchschnittlichem Klima | | 5 213 % |
| Jahreszeitbedingte Raumheizungs-Energieeffizienzklasse der Verbundanlage bei durchschnittlichem Klima | | |
| <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <input type="checkbox"/> G <small>< 30%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> F <small>≥ 30 %</small> </div> <div style="text-align: center;"> <input type="checkbox"/> E <small>≥ 34%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> D <small>≥ 36%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> C <small>≥ 75%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> B <small>≥ 82%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> A <small>≥ 90%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> A+ <small>≥ 98%</small> </div> <div style="text-align: center;"> <input type="checkbox"/> A++ <small>≥ 125%</small> </div> <div style="text-align: center;"> <input checked="" type="checkbox"/> A+++ <small>≥ 150%</small> </div> </div> | | |
| Jahreszeitbedingte Raumheizungs-Energieeffizienz der Verbundanlage bei kälterem und wärmerem Klima | | |
| Kälter: | 5 213 - 5 = | 218 % |
| Wärmer: | 5 213 + 0 = | 213 % |

Die auf diesem Datenblatt für den Produktverbund angegebene Energieeffizienz weicht möglicherweise von der Energieeffizienz nach dessen Einbau in ein Gebäude ab, denn diese wird von weiteren Faktoren wie dem Wärmeverlust im Verteilungssystem und der Dimensionierung der Produkte im Verhältnis zu Größe und Eigenschaften des Gebäudes beeinflusst.



ENERG

енергия · ενέργεια

Y



IJA





IE





IA

 WATERKOTTE


EcoTouch 5063.5T - water to water







| | | |
|---|---|-------------------------------------|
| + |  | <input type="checkbox"/> |
| + |  | <input type="checkbox"/> |
| + |  | <input checked="" type="checkbox"/> |
| + |  | <input type="checkbox"/> |





Product fiche requirements for heat pump space heaters and heat pump combination heaters (in accordance with EU regulation no. 811/2013)

| | | | | | | |
|---|--------------------|---|---------------|---------------|--|--|
| Supplier's name | | Waterkotte GmbH, Gewerkestr. 15, 44628 Herne, Germany | | | | |
| Model(s): | 1 | EcoTouch 5063.5T, Water/Water | | | | |
| | 2 | EcoTouch 5075.5T, Water/Water | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| Item | Symbol | Unit | 1 | 2 | | |
| Medium temperature / Low temperature | | | | | | |
| Seasonal space heating energy efficiency class of the model | - | - | A+++ / A+++ | A+++ / A+++ | | |
| Declared load profile for water heating | - | - | - | - | | |
| Water heating energy efficiency class | - | - | - | - | | |
| Rated heat output, including the rated heat output of any supplementary heater under average climate conditions | P _{rated} | kW | 59 / 65 | 69 / 76 | | |
| Seasonal space heating energy efficiency under average climate conditions | η _s | % | 211 / 281 | 215 / 285 | | |
| Space heating, annual energy consumption under average climate conditions | Q _{HE} | kWh | 22381 / 18580 | 25452 / 21527 | | |
| Water heating energy efficiency | η _{wh} | % | - | - | | |
| Water heating, the annual electricity consumption | AEC | kWh | - | - | | |
| Sound power level L _{WA} , indoors | L _{WA} | dB(A) | 66 | 69 | | |
| Any specific precautions that shall be taken when the heater is assembled, installed or maintained: see installation manuel Alle beim Zusammenbau, der Installation oder Wartung des Raumheizgerätes zu treffenden besonderen Vorkehrungen: siehe Installationsanleitung Les éventuelles précautions particulières qui doivent être prises lors du montage, de l'installation ou de l'entretien du dispositif de chauffage des locaux: voir manuel d'installation | | | | | | |
| Rated heat output, including the rated heat output of any supplementary heater under colder climate conditions | P _{rated} | kW | 59 / 65 | 69 / 76 | | |
| Rated heat output, including the rated heat output of any supplementary heater under warmer climate conditions | P _{rated} | kW | 59 / 65 | 69 / 76 | | |
| Seasonal space heating energy efficiency under colder climate conditions | η _s | % | 216 / 288 | 220 / 290 | | |
| Seasonal space heating energy efficiency under warmer climate conditions | η _s | % | 211 / 283 | 214 / 286 | | |
| Space heating, annual energy consumption under colder climate conditions | Q _{HE} | kWh | 28117 / 21699 | 29701 / 25231 | | |
| Space heating, annual energy consumption under warmer climate conditions | Q _{HE} | kWh | 14520 / 11970 | 16563 / 13867 | | |
| Sound power level L _{WA} , outdoors | L _{WA} | dB(A) | - | - | | |

Information requirements for heat pump space heaters and heat pump combination heaters (in accordance with EU regulation no. 813/2013)

| | | |
|-----------|---|-------------------------------|
| Model(s): | 1 | EcoTouch 5063.5T, Water/Water |
| | 2 | EcoTouch 5075.5T, Water/Water |
| | 3 | EcoTouch 5085.5T, Water/Water |
| | 4 | EcoTouch 5095.5T, Water/Water |
| | 5 | EcoTouch 5112.5T, Water/Water |
| | | |
| | | |

| | | | | | | | | | |
|--------------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| | | | | | | | | | |
| Air-to-water heat pump | - | - | - | - | - | - | - | - | - |
| Water-to-water heat pump | yes | yes | yes | yes | yes | yes | yes | yes | yes |
| Brine-to-water heat pump | - | - | - | - | - | - | - | - | - |
| Low-temperature heat pump | - | - | - | - | - | - | - | - | - |
| Equipped with a supplementary heater | - | - | - | - | - | - | - | - | - |
| Heat pump combination heater | - | - | - | - | - | - | - | - | - |

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Parameters shall be declared for average climate conditions.

| | | | | | | | | | |
|--|---|-------------------|----------|----------|----------|----------|----------|--|--|
| Item | Symbol | Unit | 1 | 2 | 3 | 4 | 5 | | |
| Rated heat output (*) | P _{rated} | kW | 59 | 69 | 77 | 87 | 102 | | |
| Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_o | | | | | | | | | |
| T _i = -7 °C | P _{dh} | kW | 52,6 | 60,9 | 67,8 | 77,2 | 90,4 | | |
| T _i = +2 °C | P _{dh} | kW | 33,7 | 39,6 | 43,9 | 50,1 | 58,8 | | |
| T _i = +7 °C | P _{dh} | kW | 34,2 | 40,2 | 44,6 | 50,9 | 59,8 | | |
| T _i = +12 °C | P _{dh} | kW | 35,2 | 41,1 | 45,9 | 52,2 | 61,3 | | |
| T _i = bivalent temperature | P _{dh} | kW | 59,4 | 68,8 | 76,6 | 87,2 | 102,2 | | |
| T _i = operation limit temperature | P _{dh} | kW | 59,4 | 68,8 | 76,6 | 87,2 | 102,2 | | |
| For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C) | P _{dh} | kW | - | - | - | - | - | | |
| Bivalent temperature | T _{biv} | °C | - | - | - | - | - | | |
| Cycling interval capacity for heating | P _{cy} | kW | - | - | - | - | - | | |
| Degradation co-efficient (**) | C _{dh} | - | 1,0 | 1,0 | 1,0 | 1,0 | 1,0 | | |
| Seasonal space heating energy efficiency | η _s | % | 211 | 215 | 212 | 209 | 207 | | |
| Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_o | | | | | | | | | |
| T _i = -7 °C | COP _d | - | 4,07 | 4,05 | 4,03 | 4,05 | 4,05 | | |
| T _i = +2 °C | COP _d | - | 5,63 | 5,76 | 5,85 | 5,57 | 5,52 | | |
| T _i = +7 °C | COP _d | - | 6,00 | 6,16 | 6,03 | 5,92 | 5,86 | | |
| T _i = +12 °C | COP _d | - | 6,72 | 6,88 | 6,77 | 6,57 | 6,49 | | |
| T _i = bivalent temperature | COP _d | - | 3,67 | 3,63 | 3,63 | 3,66 | 3,66 | | |
| T _i = operation limit temperature | COP _d | - | 3,67 | 3,63 | 3,63 | 3,66 | 3,66 | | |
| For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C) | COP _d | - | - | - | - | - | - | | |
| For air-to-water heat pumps: Operation limit temperature | TOL | °C | - | - | - | - | - | | |
| Cycling interval efficiency | COP _{cy} | - | - | - | - | - | - | | |
| Heating water operating limit temperature | WTOL | °C | 63 | 63 | 63 | 63 | 63 | | |
| Power consumption in modes other than active mode | | | | | | | | | |
| Off mode | P _{off} | kW | 0,001 | 0,001 | 0,001 | 0,001 | 0,001 | | |
| Thermostat-off mode | P _{to} | kW | 0,017 | 0,017 | 0,017 | 0,017 | 0,017 | | |
| Standby mode | P _{sb} | kW | 0,017 | 0,017 | 0,017 | 0,017 | 0,017 | | |
| Crankcase heater mode | P _{ck} | kW | - | - | - | - | - | | |
| Supplementary heater | | | | | | | | | |
| Rated heat output (*) | P _{sup} | kW | - | - | - | - | - | | |
| Type of energy input | - | - | - | - | - | - | - | | |
| Other items | | | | | | | | | |
| Capacity control | fixed/variable | - | variable | variable | variable | variable | variable | | |
| Sound power level, indoors/ outdoors | L _{WA} | dB(A) | 66 / - | 69 / - | 69 / - | 70 / - | 71 / - | | |
| Emissions of nitrogen oxides | NO _x | mg/kWh | - | - | - | - | - | | |
| For air-to-water heat pumps: Rated air flow rate, outdoors | - | m ³ /h | - | - | - | - | - | | |
| For water-brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger | - | m ³ /h | 13 | 15 | 16 | 19 | 21 | | |
| For heat pump combination heater: | - | - | - | - | - | - | - | | |
| Declared load profile | - | - | - | - | - | - | - | | |
| Daily electricity consumption | Q _{elec} | kWh | - | - | - | - | - | | |
| Water heating energy efficiency | η _{wh} | % | - | - | - | - | - | | |
| Daily fuel consumption | Q _{fuel} | kWh | - | - | - | - | - | | |
| Contact details | Waterkotte GmbH, Gewerkestr. 15, 44628 Herne, Germany | | | | | | | | |

 (*) For heat pump space heaters and heat pump combination heaters, the rated heat output P_{rated} is equal to the design load for heating P_{design}, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(T_j).

 (**) If C_{dh} is not determined by measurement then the default degradation coefficient is C_{dh} = 0,9.

Any specific precautions that shall be taken when the heater is assembled, installed or maintained: see installation manuel

Information relevant for disassembly, recycling and/or disposal at end-of-life: see installation manuel

Alle beim Zusammenbau, der Installation oder Wartung des Raumheizgerätes zu treffenden besonderen Vorkehrungen: siehe Installationsanleitung

Sachdienliche Angaben für das Zerlegen, die Wiederverwendung und/oder die Entsorgung nach der endgültigen Außerbetriebstellung: siehe Installationsanleitung

Les éventuelles précautions particulières qui doivent être prises lors du montage, de l'installation ou de l'entretien du dispositif de chauffage des locaux: voir manuel d'installation

Informations utiles pour le démontage, le recyclage et/ou l'élimination à la fin du cycle de vie de l'appareil: voir manuel d'installation

